

TECHNICAL PARAMETERS Amplifier BAA 120

Continuous sine output power _{RMS} , max.	120 VA
Frequency range (small signal / full power)	DC - 100 kHz / 40 Hz - 25 kHz
Voltage-/Current mode	yes/yes
Output voltage _{RMS} , max.	22 V
Output current _{RMS} , max.	5.5 A
Optimum load impedance	4 Ohm
Signal input voltage _{PK} (at 1 kHz sine for max. power)	3.5 V
Distortion (frequency range 40 Hz to 5 kHz)	< 0.05 %
Signal to noise ratio	> 100 dB
Total mass	9 kg
Dimensions (WxHxD)	440 x 90 x 290 mm
Power supply Amplifier	1~ / N / PE 230 V±5% 50/60 Hz, CEE 7/7
Recommended fuse protection	16 A slow
Max. power consumption at 230 V (at full load)	230 VA
Max. power consumption at 230 V (at operation with vibration test system TV 51110)	80 VA
Interlocks:	Overload, temperature, clipping

Features:

- TIRA analog amplifiers can be adapted to all permanent magnet driven shakers on the market
- High Signal to noise ratio of > 100 dB
- Low distortion factor of < 0.05 %
- OLED display panel
- Safety management system monitors functions as temperature, overcurrent and clipping
- Selectable operating voltage ranges (100 V, 120 V or 230 V factory-set)
- Operation switchable to current- or voltage mode
- Adjustable current limit
- Phasing between input- and output signal 180° switchable
- Power cable length 1.5 m with CEE 7/7 connector (or customer request)

